

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT IDENTIFICATION AND USE					SECTION 6 - TOXICOLOGICAL PROPERTIES																																																	
MATERIAL IDENTIFIER Air Techniques Fixer Code 2					Air Techniques Fixer Code 2																																																	
Distributed By: AIR TECHNIQUES, INC					ROUTE OF ENTRY SKIN CONTACT [X] SKIN ABSORPTION [X] EYE CONTACT [X] INHALATION ACUTE [X] INHALATION CHRONIC [X] INGESTION [X]																																																	
1295 WALT WHITMAN RD					EFFECTS OF ACUTE EXPOSURE TO MATERIAL																																																	
MELVILLE, NY 11747 (516) 433-7676					EYE - Irritation or burning may occur. High concentrations of acetic acid vapors can cause excess blinking, tearing, and eye discomfort.																																																	
CHEMTREC (800) 424-9300					SKIN - Irritation and burning possible.																																																	
SECTION 2 - HAZARDOUS INGREDIENTS					INGESTION - Acetic Acid can cause burning to mouth, throat, and esophagus. Nausea, vomiting, abdominal pain, shock state collapse are possible. Sodium Sulfite may cause circulatory disturbances and central nervous system damage.																																																	
SECTION 3 - PHYSICAL DATA					INHALATION - If heated ammonia vapors will irritate the throat.																																																	
HAZARDOUS INGREDIENTS					EFFECTS OF CHRONIC EXPOSURE TO MATERIAL None																																																	
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>HAZARDOUS INGREDIENTS</th> <th>%</th> <th>UN, NA, OR CAS NUMBER</th> <th>OSHA PEL</th> <th>ACGIH TLV</th> <th>LD₅₀ OF MATERIAL mg/kg (SPECIFY SPECIES/ROUTE)</th> <th>LC₅₀ OF MATERIAL (SPECIFY SPECIES)</th> </tr> </thead> <tbody> <tr> <td>Water</td> <td>60-100</td> <td>7732-18-5</td> <td>---</td> <td>---</td> <td>---</td> <td>---</td> </tr> <tr> <td>Ammonium Thiosulfate</td> <td>1-5</td> <td>7783-18-8</td> <td>N/A</td> <td>N/A</td> <td>Oral/Rat 2890</td> <td>N/A</td> </tr> <tr> <td>Sodium Sulfite</td> <td>1-5</td> <td>7757-83-7</td> <td>N/A</td> <td>N/A</td> <td>IVH/Rat 115</td> <td>N/A</td> </tr> <tr> <td>Sodium Acetate</td> <td>1-5</td> <td>127-09-3</td> <td>N/A</td> <td>N/A</td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table>					HAZARDOUS INGREDIENTS	%	UN, NA, OR CAS NUMBER	OSHA PEL	ACGIH TLV	LD ₅₀ OF MATERIAL mg/kg (SPECIFY SPECIES/ROUTE)	LC ₅₀ OF MATERIAL (SPECIFY SPECIES)	Water	60-100	7732-18-5	---	---	---	---	Ammonium Thiosulfate	1-5	7783-18-8	N/A	N/A	Oral/Rat 2890	N/A	Sodium Sulfite	1-5	7757-83-7	N/A	N/A	IVH/Rat 115	N/A	Sodium Acetate	1-5	127-09-3	N/A	N/A	N/A	N/A	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>SENSITIZATION PROPERTY</th> <th>CARCINOGENICITY</th> <th>REPRODUCTIVE EFFECTS</th> <th>SYNERGISTIC EFFECTS</th> <th>IRRITANCY</th> </tr> </thead> <tbody> <tr> <td>N/A</td> <td>None</td> <td>None</td> <td>None</td> <td>Eye and skin possible</td> </tr> </tbody> </table>					SENSITIZATION PROPERTY	CARCINOGENICITY	REPRODUCTIVE EFFECTS	SYNERGISTIC EFFECTS	IRRITANCY	N/A	None	None	None	Eye and skin possible
HAZARDOUS INGREDIENTS	%	UN, NA, OR CAS NUMBER	OSHA PEL	ACGIH TLV	LD ₅₀ OF MATERIAL mg/kg (SPECIFY SPECIES/ROUTE)	LC ₅₀ OF MATERIAL (SPECIFY SPECIES)																																																
Water	60-100	7732-18-5	---	---	---	---																																																
Ammonium Thiosulfate	1-5	7783-18-8	N/A	N/A	Oral/Rat 2890	N/A																																																
Sodium Sulfite	1-5	7757-83-7	N/A	N/A	IVH/Rat 115	N/A																																																
Sodium Acetate	1-5	127-09-3	N/A	N/A	N/A	N/A																																																
SENSITIZATION PROPERTY	CARCINOGENICITY	REPRODUCTIVE EFFECTS	SYNERGISTIC EFFECTS	IRRITANCY																																																		
N/A	None	None	None	Eye and skin possible																																																		
N/A = Not Available					SECTION 7 - PREVENTIVE MEASURES																																																	
SECTION 4 - FIRE AND EXPLOSION DATA					GLOVES																																																	
FLAMMABILITY YES [] NO [X] IF YES, UNDER WHICH CONDITION					Nitrile Rubber or Plastic																																																	
MEANS OF EXTINCTION					RESPIRATOR Use NIOSH approved cartridge																																																	
Any applicable to the primary cause of fire.					respirator in poorly ventilated areas.																																																	
FLASH POINT (°C) METHOD USED N/A					EYE Eye wash station and chemical splash goggles.																																																	
UPPER EXPLOSION LIMIT (% BY VOLUME) N/A LOWER EXPLOSION LIMIT (% BY VOLUME) N/A					FOOTWEAR N/A																																																	
AUTOIGNITION TEMPERATURE (°C) N/A					CLOTHING Cover skin																																																	
TDG FLAMMABILITY CLASSIFICATION N/A HAZARDOUS COMBUSTION PRODUCTS N/A					OTHER N/A																																																	
EXPLOSION SENSITIVITY TO IMPACT DATA N/A					ENGINEERING CONTROLS Recommended ventilation - 10 room volumes per hour																																																	
RATE OF BURNING N/A EXPLOSIVE POWER N/A SENSITIVITY TO STATIC DISCHARGE N/A					LEAK AND SPILL PROCEDURE Neutralize with sodium bicarbonate, dike the spill and soak up with absorbent material. Put into plastic container for legal disposal.																																																	
SECTION 5 - REACTIVITY DATA					WASTE DISPOSAL Disposal must conform to Federal and Local Regulations. Consult local sewer authority.																																																	
CHEMICAL STABILITY YES [X] NO [] IF NO, UNDER WHICH CONDITIONS					HANDLING PROCEDURES AND EQUIPMENT Store and handle in a tightly capped container. Wear protective gloves, clothes, and goggles. Keep work space uncluttered. Avoid contact with eyes and skin.																																																	
INCOMPATIBILITY WITH OTHER SUBSTANCES YES [X] NO [] IF YES, WHICH ONES Strong Alkalies or Acids					STORAGE REQUIREMENTS Do not store near food, drink, or tobacco products. Store in a well ventilated area. Store between 10 - 25 °C. Do not allow to freeze.																																																	
REACTIVITY, AND UNDER WHAT CONDITIONS Will neutralize strong alkalis and release some heat.					SPECIAL SHIPPING INFORMATION Ship above 4.4 °C. Protect from puncturing by handling or other equipment.																																																	
HAZARDOUS DECOMPOSITION PRODUCTS Sulfur Dioxide (acids) and ammonia (alkalis).					SECTION 8 - FIRST AID MEASURES																																																	
					EYES - Flush with water for at least 15 minutes. Get medical attention.																																																	
					SKIN - Remove contaminated clothing and wash skin thoroughly with soap and water. Wash clothes before re-use.																																																	
					INHALATION - Remove to fresh air. If breathing becomes difficult, give oxygen. Get medical attention.																																																	
					INGESTION - If conscious, give large amounts of water. Do not induce vomiting. If not conscious, give artificial respiration. Obtain prompt medical attention.																																																	
					SECTION 9 - PREPARATION OF MSDS																																																	
					Form Preparation Controlled by FILM PROCESSOR DEPARTMENT																																																	
					TELEPHONE NO. (516) 433-7676																																																	
					DATE 10-4-13																																																	

